HSM SECURIO P36i

Professional shredder

Large Volume, High Performance





- Uses Energy Management Control System (EMCS) to deal with energy in a sensible manner by reducing energy consumption up to 30%
- Automatically switches to energy saving mode in 2 minutes after last use, switches off entirely if not used for 4 hours; temporary mode for small shredding jobs; and permanent mode for large shredding jobs
- High quality materials and "Made in Germany" quality for safety and durability.
- Integrated automatic oiler provides for consistently high cutting capacity. (HSM1853, HSM1852, HSM1855)
- The innovative drive and operating concept IntelligentDrive offers silent, standard and performance operating modes for destroying data efficiently and comfortably.
- Intuitive operation and menu selection via the high resolution touch display
- Powerful motor allows for continuous operation
- Cutting rollers are V-Tek by HSM with specially hardened steel rollers. This optimum design of all cutting unit components saves valuable energy.
- Equipped with Anti-Jam technology to easily and quickly reverse out paper in the event the machine is overloaded
- Includes a removable bag frame
- Uses a 58 gallon capacity shred bag; Part #HSM2117



| HSM part# | HSM1850 | HSM1851 | HSM1853 | HSM1852 | HSM1855 |
|------------------------------------|-----------------------|----------------------|--------------------------------|--------------------------------|-----------------------|
| Cutting type | Strip cut | Strip cut | Cross cut | Micro cut | High Security P-6 |
| Cutting size | 1/8" | 1/4" | 3/16" x 1 1/8" | 1/16" x 9/16" | 1/32" x 7/16" |
| Security level DIN 32757-1 | 2 | 2 | 3 | 4 | 5 |
| Security level DIN 66399 | P-2 / O-2 / T-2 / E-2 | P-2 /O-2 / T-2 / E-2 | P-4 / O-3 / T-4 / E-3 / F-1 | P-5 / O-4 / T-5 / E-4 / F-2 | P-6 / T-6 / E-5 / F-3 |
| Cutting capacity per run in sheets | 37-39^ | 47-49^ | 29-31^ | 18-20^ | 11-12^ |
| Cutting speed | 18 ft/min | 18 ft/min | 18 ft/min | 18 ft/min | 18 ft/min |
| Throat opening | 13" | 13" | 13" | 13" | 13" |
| Motor power (hp) | 2.15 | 2.15 | 2.15 | 2.15 | 2.15 |
| Voltage | 115V / 60 Hz | 115V / 60 Hz | 115V / 60 Hz | 115V / 60 Hz | 115V / 60 Hz |
| Dimensions (HxWxD) | 40.16"x22.8"x21.7" | 40.16"x22.8"x21.7" | 40.16"x22.8"x21.7" | 40.16"x22.8"x21.7" | 40.16"x22.8"x21.7" |
| Weight | 141 lbs | 141 lbs | 150 lbs | 150 lbs | 150 lbs |
| Shred-bin volume | 38.3 gallons | 38.3 gallons | 38.3 gallons | 38.3 gallons | 38.3 gallons |
| Cutting capabilities | 141 lbs | 141 lbs | 150 lbs | 150 lbs | 150 lbs |
| Shred bin volume | 38.3 gallons | 38.3 gallons | 38.3 gallons | 38.3 gallons | 38.3 gallons |
| Cutting capabilities | Ů⊘⊓∎҈∙ | ௺₡௱℡℗℮ | Ů∥⊓₽€ | <u>ا الما @الاً</u> | ௺௰௫ |

All technical specifications are approximate values. Technical and design modifications reserved. ^Sheet capacity will vary depending on paper size, weight, quality and proper power supply

HSM of America, LLC 419 Boot Road Downingtown, PA 19335 www.hsm.us Customer Service: 800.613.2110

